


WoodenBoat Regatta Series



2009 Measurement Sheet and Roster Information

Name of vessel _____ Sail Number _____
 Rig _____ Year Built _____ Designer _____ Builder _____
 Hull Color _____ Deck Color _____ Construction _____
 Owner's Name _____ Class or Type _____
 Address _____ E-mail _____
 Telephone (____) _____
 Cell (____) _____

All measurements in feet and inches, to the nearest inch.

Hull Measurements (turn over for explanations)

LOA: _____ (excluding bowsprits and/or boomkins)
 LWL: _____ BEAM: _____ (excluding rubrails)
 DRAFT: _____ (centerboard up, if applicable)
 Propeller type: ___ Fixed ___ Folding ___ Feathering ___ None/Installation: ___ In aperture ___ Exposed
 Number of Blades: ___ Two ___ Three ___ Four
 Displacement in lbs. (if known): _____

Rig Measurements (Complete appropriate section only)

Schooner:

Check below if gaff-headed:
 ___ Main ___ Fore ___ Mizzen
 P2 _____ if three masted,
 J _____ mizzen:
 P _____ PY _____
 B _____ BY _____
 P1 _____
 P3 _____
 B1 _____

Ketch, Yawl, Sloop, or Cutter:

Check Type:
 ___ Ketch ___ Yawl ___ Sloop ___ Cutter
 Check if gaff-headed:
 ___ Main ___ Mizzen
 P2 _____
 J _____
 P _____ PY _____
 B _____ BY _____

For All Rigs P2(spin) _____ SPL _____ see definitions

Signature of Owner: _____ Date: _____

To obtain a rating certificate, mail this completed form along with a check in the amount of \$25.00 (payable to CRF Group) to the following address:

CRF GROUP
 PO BOX 319
 MYSTIC, CT 06355-0319
 Tel. 860.460.3990 Fax 860.572.9271 E-mail: mischief@snet.net

Rig Definitions

P2 Distance from highest halyard block for headsails to main deck.

P2(spinnaker halyard block to main deck, if higher than P2).

J Horizontal distance from forward side of foremost mast to the intersection of the forwardmost stay with the deck, stem, or bowsprit.

SPL Length of Spinnaker Pole, if longer than J.

P Hoist of mainsail. (To peak halyard block for gaff-rigged sails)

B Distance from afterside of mainmast to position to which mainsail clew can be extended.

P1 Distance from top of foreboom to the highest halyard block used for sail on the after side of the foremast.

P3 Distance from the top of the foreboom, or extension thereof when foreboom is resting parallel to waterline, to the highest halyard block used for sail forward of the mainmast. If no fisherman is carried, use highest halyard block on the afterside of the mainmast.

B1 Distance from the foreside of the mainmast to afterside of the foremast.

PY Hoist of mizzensail. (To peak halyard block on mast for gaff-rigged vessels)

BY Distance from afterside of mizzenmast to position to which mizzen clew can be extended.

